Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for improving utilization in a peer-to-peer network having a plurality of nodes, the method comprising:

allocating assigning one or more storage slots at to each node in the peer-to-peer network, a first portion of the storage slots allocated for hosting storage zones and any remaining storage slots at each node allocated as a free slot reserve storage slot;

inserting data into the storage zones; and when a storage zone reaches its full capacity,

splitting the data in the storage zone into a first and second portion, allocating converting a free slot reserve storage slot as into a new storage zone, and

transferring the second portion of the data to the new storage zone.

- 2. (Currently Amended) The method of claim 1 wherein each node is allocated assigned more storage slots than its actual physical capacity allows.
- 3. (Original) The method of claim 2 wherein each node is allocated N-1 virtual slots for each N storage slots allocated.
- 4. (Original) The method of claim 2 wherein a storage zone at a node is transferred to another node in the peer-to-peer network if the data inserted into the storage zones at the node fills the actual physical capacity of the node.
- 5. (Original) The method of claim 4 where a local search for candidate nodes in a transfer set is conducted prior to transfer of the storage zone.

- 6. (Currently Amended) The method of claim 1 wherein the new storage zone is transferred to a free slot reserve <u>storage slot</u> on a different node when the storage zones hosted at the node exceed[[s]] the <u>storage</u> slots allocated at the node.
- 7. (Original) The method of claim 6 where a local search for candidate nodes in a transfer set is conducted prior to transfer of the new storage zone.
- 8. (Original) The method of claim 1 wherein the data is associated with hashkeys of a hash function and where each storage zone is responsible for a subset of all hashkeys.
- 9. (Original) The method of claim 8 wherein the hashkeys are uniformly distributed by the hash function.
- 10. (Original) The method of claim 1 wherein the storage slots are of a fixedsize.
- 11. (Currently Amended) A method for improving utilization in a peer-to-peer network, the method comprising:

assigning one or more storage slots at <u>to</u> each node in the peer-to-peer network, a first portion of the storage slots allocated for <u>hosting</u> storage zones and any remaining storage slots at each node allocated as a free slot reserve storage slot; and

when a new node is added to the peer-to-peer network, transferring at least one storage zone from another node in the peer-to-peer network to the new node so as to maintain at least one storage slot at each node in the peer-to-peer network.

- 12. (Original) The method of claim 11 wherein the storage zone at the another node is eagerly split into a first and second portion with the second portion transferred to the new storage zone at the new node.
- 13. (Original) The method of claim 12 wherein each node maintains no more than one eagerly split zone.
- 14. (Original) The method of claim 11 wherein the another node has two or more storage zones and one of these storage zones is transferred to the new node to become the new storage zone on the new node.
- 15. (Original) The method of claim 11 wherein a search is conducted among a local set of nodes in the peer-to-peer network for a storage zone to transfer to the new node.
- 16. (Currently Amended) A node for a peer-to-peer network, the node maintaining assigned a number of slots for storage of objects in the peer-to-peer network where the number of slots a capacity of the number of slots exceeds the node's an actual physical storage capacity of the node.
- 17. (Original) The node of claim 16 where the number of slots maintained by the node is equal to 2xN-1 where N is a number of slots that would fill the node's actual physical storage capacity.
- 18. (Currently Amended) The node of claim 16 where the objects stored in a slot one of the number of slots at the node are transferred to another node in the peer-to-peer network if the objects inserted into stored in the slots at the node fill[[s]] the actual physical capacity of the node.

- 19. (Original) The node of claim 16 wherein the objects are associated with hashkeys of a hash function and where each node is responsible for a subset of all hashkeys.
- 20. (Original) The node of claim 16 wherein the slots are of a fixed-size.
- 21. (Currently Amended) The method of claim 1, wherein each storage zone[[(s)]] is located within a particular physical node.
- 22. (Currently Amended) The method of claim 21, wherein each storage slot[[(s)]] is located within a particular physical node.
- 23. (Currently Amended) The method of claim 11, wherein each storage zone[[(s)]] is located within a particular physical node.
- 24. (Currently Amended) The method of claim 23, wherein each storage slot[[(s)]] is located within a particular physical node.
- 25. (Currently Amended) The method of claim 1, wherein a zone is hosted within a slot and the slot(s) size a size of the slot is a system wide constraint representing the limit size to which a zone can grow before it fills the slot and must be split.
- 26. (Currently Amended) The method of claim 11, wherein a zone is hosted within a slot and the slot(s) size a size of the slot is a system wide constraint representing the limit size to which a zone can grow before it fills the slot and must be split.
- 27. (Previously Presented) The method of claim 16 wherein there are one or more real slots that consume the entire actual physical capacity of the node and

one or more virtual slots that have no actual physical storage capacity associated with them.